

Vicoll DATA SHEET


Connecto® I PVC grating for swimming-pool and pedestrians - white colour - class A15

Code: GR77PB









■ FUNCTION:

The grating is designed to drain run-off water. In accordance with EN1433 standard and the C marking, it can be used in private areas for all building applications, the environment of home, parks and gardens in class A15.

■ DESCRIPTION:

This grating class A15 is injected in white PVC with anti-UV treatment.

ACCESSORIES:

This grating can be installed with these types of drainage channel:

- High channel body Connecto width 130: CAN177 and KCAN177N
- Shallow channel body Connecto width 130: CAB773, CABS773 and CAB133A

To fix a grating on CAB133A, it's necessary to use one FIXCAB13 (locking system with galvanized screw).

To fix a grating on CAN177, KCAN177N, CAB773 and CAB\$773, it's necessary to use two FIXCAN (set made up of one screw).

Bituminous Paved

Bituminous Paved

.,


■ CHARACTERISTICS:

Resistance class: A15

Width: 128 mm Length: 500 mm Overall height: 20 mm Grating type: PVC

Drainage surface: 232 cm²/ml Opening dimensions: ≤ 8 mm

Weight: 0,5 kg



CAN177

KCAN177N

CABS773

CAB133A

Bituminous Paved area

■ IMPLEMENTATION:

- 1. See the installation scheme opposite with the channel CAN177 and KCAN177N.
- 2. See the installation scheme opposite with the channel CAB773 and CABS773.
- 3. See the installation scheme opposite with the channel CAB133A.
- 4. If you don't use Connecto channel, please leave a space between gratings to allow a free expansion.

QUALITY - ENVIRONMENT:



DATE: August 2015



Head office and Plants: 37, rue Pierre et Marie Curie - BP 10966 - 49309 CHOLET Cedex

Email: export.nicoll@aliaxis.com

NON CONTRACTUAL DOCUMENT _____

an OAliaxis company